

RAILWAY-CERTIFIED ROUTER

POWERFUL MODULAR ONBOARD ROUTING PLATFORM FOR SECURE IOT COMMUNICATION, FLEET MANAGEMENT & INFOTAINMENT APPLICATIONS

PRODUCT DESCRIPTION

The wireless railway router from Mission Embedded is a versatile onboard routing platform specifically designed for rail environments. Its high modularity in terms of performance, functionality, extensions and services make it an ideal solution for any customer-

specific requirements.

The ruggedized router is compliant with EN 50121, EN 50155 and can be utilized for a variety of use cases – from Mission-critical Applications to Passenger WiFi or Infotainment Systems.



APPLICATIONS

- Mission critical communication like Telemetry or remote-control applications
- Passenger Wi-Fi
- Video Surveillance
- Passenger Infotainment

KEY FEATURES AND ADVANTAGES

HIGH MODULARITY

- Customer-specific performance and functionality features
- Wide range of optional services and extensions
- Large variety of Radio Modules (e.g. 5G, LTE, SDR)
- Extended storage (SSD)

RELIABLE AND SECURE IP COMMUNICATION

- Multi-link aggregation for high availability and increased Bandwidth
- Certifiable to IEC 62443-4-2 SL2 Security-Level
- Hardened Linux Platform
- Trusted Platform Module (TPM) for secure applications
- Software Defined Networking (SDN) capability

RUGGED RAILWAY-CERTIFIED DESIGN

- Compliant with EN 50121/50155/45545 Railway Standards
- Suitable for versatile Railway Applications
- Wide operating temperature: -25° to +70°C
- Wide input voltage range
- Aluminium housing with fan-less cooling

COST-EFFECTIVE AND SAFE OPERATION

- Fleet Management Tool
- Easy configuration and maintenance (fail-safe software update)
- Retrofittable on existing fleets
- Short time to market
- Optional Safety Extensions

SPECIFICATIONS

SYSTEM	
CPU	Multiple CPUs available (ARM, Intel) Standard: Intel Atom® Quad-Core Processor - 1.6 GHz
Flash Memory	Depending on customer requirements
Mission Embedded Technologies	<ul style="list-style-type: none"> ▪ ME Enhanced Linux Platform ▪ ME Routing Platform
User Applications	Support for user applications and scripts
Software Update	<ul style="list-style-type: none"> ▪ Remote Software and Firmware Update ▪ ME fail-safe Over-the-Air Software Update (on request)
Parameterization	Switchless via USB / remote via Management GUI or SSH
Reliability	MTBF depending on configuration

SOFTWARE									
Network Services	<ul style="list-style-type: none"> ▪ IP Address Assignment statically or via DHCP ▪ Port- and tag-based VLAN, VLAN configurable ▪ Prioritization of Data Streams/QoS levels (high/medium/low) ▪ ME LTE Link Bandwidth Aggregation (optional) ▪ NTP Client/Server 								
Security	<table border="0"> <tr> <td style="vertical-align: top;">Firewall</td> <td> <ul style="list-style-type: none"> ▪ Flexible configuration via web interface or CLI ▪ Flexible handling of zones ▪ SPI, Anti-DoS Attack ▪ Filtering Multicast, Ping package, Access Control List (ACL) ▪ NAT, PAT, DMZ, Port Mapping, Virtual Server </td> </tr> <tr> <td style="vertical-align: top;">Multi Level Authority</td> <td></td> </tr> <tr> <td style="vertical-align: top;">AAA</td> <td> <ul style="list-style-type: none"> ▪ IEEE 802.1x Authentication ▪ Authentication via PSK (WPA/WPA2 Enterprise) and certificate-based (optional) ▪ RADIUS Client Functionality (optional) ▪ Network Authentication and Authorization EAP-TLS (optional) </td> </tr> <tr> <td style="vertical-align: top;">Data Security</td> <td> <ul style="list-style-type: none"> ▪ IPSec, OpenVPN, WireGuard, PPTP, GRE (optional) </td> </tr> </table>	Firewall	<ul style="list-style-type: none"> ▪ Flexible configuration via web interface or CLI ▪ Flexible handling of zones ▪ SPI, Anti-DoS Attack ▪ Filtering Multicast, Ping package, Access Control List (ACL) ▪ NAT, PAT, DMZ, Port Mapping, Virtual Server 	Multi Level Authority		AAA	<ul style="list-style-type: none"> ▪ IEEE 802.1x Authentication ▪ Authentication via PSK (WPA/WPA2 Enterprise) and certificate-based (optional) ▪ RADIUS Client Functionality (optional) ▪ Network Authentication and Authorization EAP-TLS (optional) 	Data Security	<ul style="list-style-type: none"> ▪ IPSec, OpenVPN, WireGuard, PPTP, GRE (optional)
Firewall	<ul style="list-style-type: none"> ▪ Flexible configuration via web interface or CLI ▪ Flexible handling of zones ▪ SPI, Anti-DoS Attack ▪ Filtering Multicast, Ping package, Access Control List (ACL) ▪ NAT, PAT, DMZ, Port Mapping, Virtual Server 								
Multi Level Authority									
AAA	<ul style="list-style-type: none"> ▪ IEEE 802.1x Authentication ▪ Authentication via PSK (WPA/WPA2 Enterprise) and certificate-based (optional) ▪ RADIUS Client Functionality (optional) ▪ Network Authentication and Authorization EAP-TLS (optional) 								
Data Security	<ul style="list-style-type: none"> ▪ IPSec, OpenVPN, WireGuard, PPTP, GRE (optional) 								
Reliability	<ul style="list-style-type: none"> ▪ ME Mobile Link Monitoring - for monitoring of mobile radio links (optional) ▪ ME Mobile Fast Link Fail-Over - in case of interruptions or failure of mobile radio link (optional) ▪ Auto-recovery from failure ▪ Watchdog ▪ ME Automatic changeover between radio connections (optional) 								
Wi-Fi	<ul style="list-style-type: none"> ▪ Wi-Fi Captive Portal ▪ Flexible Wi-Fi Hotspot Configuration ▪ ME Traffic Shaping / Fair Bandwidth Distribution for Wi-Fi Clients 								
Routing	<ul style="list-style-type: none"> ▪ Static / Extended / Multipath / Multipath TCP Routing ▪ Virtual Router Redundancy Protocol (VRRP) for Router Redundancy (optional) ▪ ME GEO based Routing (optional) 								

FLEET MANAGEMENT (OPTIONAL)

- Web-based application
- Hosting on Mission Embedded's cloud or on the operator's infrastructure

CONNECTORS AND INTERFACES (STANDARD CONFIGURATION)

All connectors are protected against polarity reversal.

Power Supply	M12 S-coded 4-pin male connector
Gigabit Ethernet Interface	2 x M12 X-coded 8-pin female connector. Depending on configuration up to 2 GbE interfaces supported.
USB Interface	1 x M12 A-coded 5-pin female USB 2.0 connector
Antenna Connections	Wireless Interface Connector Type: Standard 4 x TNC female Mobile Main: Mobile Antenna Connector Mobile Aux: Mobile Antenna Connector WIFI A1: WiFi 1 Antenna Connector WIFI A2: WiFi 2 Antenna Connector
Input/Output Interface	1 x SUB-D female 9-pin with ▪ 2 x Digital Outputs (potential-free) ▪ 4 x Digital Inputs
LED Indicators	8 LEDs ▪ 1 x Router Power Status Indicator (PWR) ▪ 7 x Customized Status LEDs
Modularity	Combination of up to 6 wireless modules per router possible
Wi-Fi	Up to 2 modules Standard: IEEE 802.11a/b/g/n/ac (Wi-Fi 5) / Dual-band 2.4 or 5 GHz
Mobile (4G/5G)	Up to 2 WWAN modules Standard: LTE with up to 150 Mbps DL / 50 Mbps UL per module
SIM Holder	4 x SIM Card Holders front side (WWAN details on request)
GNSS Positioning	On request

POWER SUPPLY

Input Voltage (nominal)	24 VDC - according to EN 50155 Standard
Voltage Range	9 to 36 VDC Additional ranges on request (18 to 75 / 40 to 160 VDC)
Power Consumption	Maximum: 20 W (depending on configuration) Standby: 5 W
Galvanic Isolation	Compliant with EN 50155
Interruptions of Voltage Supply	EN50155 Class S2, no battery installed
Protective Earthing	Supported
Power Connector	M12 S-coded male
Reverse Polarity Protection	Supported

CUSTOMIZATION

Extensions	<ul style="list-style-type: none"> ▪ SSD (up to 1 TB), e.g. for caching of online data ▪ IBIS Interface ▪ CAN Interface ▪ RS-422/485 Interface, SUB-D 9-pin ▪ SCEP Support ▪ Mobile IP Support
-------------------	--

ENVIRONMENTAL CONDITIONS

Operating Temperature	-25 to 70°C - EN 50155 class T3
Storage Temperature	-40 to 85°C
Ambient Relative Humidity	10 to 95% (non-condensing)
Shock and vibration	Conform to EN 50155 (testing according to EN 61373)
IP Level	IP20
Railway Fire Protection	EN 45545-2 HL2

STANDARDS AND CERTIFICATIONS

Shock and Vibration	EN 61373:2010
EMC	EN 61000-6-2 EN 61000-6-4
EMS	EN 61000-4-2 EN 61000-4-3 EN 61000-4-4 EN 61000-4-5 EN 61000-4-6
Radio	Depending on configuration
CE	2014/30/EU (Electromagnetic Compatibility Directive) 2014/35/EU (Low Voltage Directive) 2011/65/EU (RoHS)
Railway	EN 50155, EN 50121-3-2
Railway Fire Protection	EN 45545-1, EN 45545-2 HL3, EN 45545-5

MECHANICAL DATA

Dimensions (W/L/H)	225 × 190 × 95 mm (housing) 200 × 95 mm (front panel)
Housing	Anodized Aluminum
Weight	2.8 kg (depending on configuration)
Installation	360° mounting option using 4 screws. Minimum distances: 20 cm to front, 10 cm to other sides

THERE IS ALWAYS A MISSION EMBEDDED

Mission Embedded develops and supplies highly reliable embedded systems for professional applications in safety-critical areas such as railway and transportation, special vehicles, industry, medical technology as well as aerospace and defense. Our high-quality tailor-made solutions enable our customers to turn their innovation projects into reality within the shortest possible time.

© Mission Embedded GmbH. All rights reserved. V1.1 - Updated on 20.06.2023

This document or parts of it may not be reproduced or otherwise used without the explicit and written permission of Mission Embedded GmbH. Product specifications subject to change without notice.