

# AI RAILWAY COMPUTING PLATFORM

## HIGH-PERFORMANCE COMPUTING PLATFORM FOR SAFETY-CRITICAL COMPUTER VISION APPLICATIONS

### PRODUCT DESCRIPTION

The AI Railway Computing Platform from Mission Embedded is specifically designed for advanced computer vision and intelligent video analysis in safety-critical railway applications. With the ability to be installed in network-based clusters, the compact NVIDIA-based platform provides ultra-fast high-performance

computing to process massive multi-dimensional sensor data in real time. The rugged platform offers a high level of customization in terms of performance, functionality, and services. It meets the safety requirements of SIL 2 and the standards, including EN 50155 and fire protection standard EN 45545.



Cluster Illustration

### RAILWAY APPLICATIONS

- Obstacle detection and classification
- Collision avoidance
- Signal recognition
- Autonomous driving (shunting)
- High-definition railroad mapping
- Real-time infrastructure monitoring for predictive maintenance
- Driver vigilance
- Passenger compartment monitoring
- High-performance data recording

### KEY FEATURES AND ADVANTAGES

**HIGH PERFORMANCE**

- NVIDIA ARM® CPU/GPU
- Clustering option for high-performance computing
- GigE Vision® standard for fast image transfer
- Hardware computer vision and AI accelerators
- High-performance storage options

**RELIABLE AND SAFE OPERATION**

- Safety controller for supervision
- High reliability for safety applications
- High availability for mission-critical applications (clustering option)
- Hot/cold stand-by or two-channel design
- Designed for SIL2 applications

**RUGGED RAILWAY-CERTIFIED DESIGN**

- Compliant with EN 50121/50155/45545 Railway Standards
- ECE R10 regulation compliance, e-marking
- Shock and vibration resistant
- Robust housing and small form factor
- Designed for high-density rack mounting

**HIGH COST-EFFECTIVENESS**

- Short time-to-market
- Long-term availability and lifecycle management
- Mean time between failure (MTBF): 300.000-400.000 h (depending on configuration)
- Mean time to repair (MTTR): less than 15 minutes

## SPECIFICATIONS

SYSTEM	
<b>CPU</b>	Multiple CPUs available (ARM) Standard: NVIDIA® 8-core ARM® v8.2 64-bit CPU, 8MB L2+4MB L3, 2260 MHz
<b>GPU</b>	Multiple GPUs available Standard: NVIDIA® 512-core GPU
<b>Flash Memory</b>	Multiple options available Standard: 32 GB
<b>Storage</b>	Internal M.2 NVMe
<b>Video Codecs</b>	JPEG, H.264, H.265 / HEVC
<b>Vision Accelerator</b>	Dedicated co-processor & ISP
<b>AI Inference Accelerator</b>	Two accelerators, 10 TOPS (INT8) in total
<b>Auxiliary Co-Processing</b>	Two 32-bit ARM® Cortex-R5
<b>Reliability</b>	MTBF: 300.000-400.000h depending on configuration
<b>Availability</b>	<ul style="list-style-type: none"> <li>▪ MTTR: less than 15 minutes</li> <li>▪ Designed for cluster operation: load-balance, hot/cold standby</li> </ul>
<b>Safety Co-controller</b>	<ul style="list-style-type: none"> <li>▪ 32-bit ARM® Cortex-M7 CPU running at up to 216 MHz</li> <li>▪ Pre-certified self-test library</li> <li>▪ Mission Embedded System-on-Module application supervision framework for SIL2 applications</li> <li>▪ EN 50159, category 1, black channel communication framework</li> </ul>
<b>Security</b>	TPM 2.0 module

SOFTWARE	
<b>Mission Embedded Technologies</b>	ME enhanced Linux Platform
<b>User Applications</b>	Support for user applications and scripts
<b>Software Update</b>	<ul style="list-style-type: none"> <li>▪ Remote software and firmware update</li> <li>▪ ME fail-safe over-the-air software update (on request)</li> </ul>
<b>Parameterization</b>	Switchless via USB / remote via Management Web-GUI or SSH
<b>Fleet Management (optional)</b>	Web-based application
<b>Video Applications</b>	<ul style="list-style-type: none"> <li>▪ GigE Vision® protocol stack</li> <li>▪ Image pre-processing</li> <li>▪ Video codec framework</li> </ul>

CONNECTORS AND INTERFACES (STANDARD CONFIGURATION)	
<b>All connectors are protected against polarity reversal.</b>	
<b>Power Supply</b>	M12 S-coded 4-pin male connector
<b>Gigabit Ethernet Interface</b>	<ul style="list-style-type: none"> <li>▪ 1 x M12 X-coded 8-pin female connector (2500/1000/100/10 Mbit/s)</li> <li>▪ 1 x M12 X-coded 8-pin female connector (1000/100/10 Mbit/s)</li> </ul>
<b>Input/Output Interface</b>	<ul style="list-style-type: none"> <li>▪ 2 x digital inputs</li> <li>▪ 1 x CAN interface</li> </ul>

**POWER SUPPLY**

<b>Input Voltage (nominal)</b>	24 VDC (according to EN 50155 Standard)
<b>Voltage Range</b>	16.8 to 32 VDC Additional ranges on request (18 to 75 / 40 to 160 VDC)
<b>Power Consumption</b>	Maximum: 60 W (depending on configuration) Standby: 1.4 A under load - 0.4 in idle mode
<b>Galvanic Isolation</b>	Compliant with EN 50155, all external connectors
<b>Interruptions of Voltage Supply</b>	EN 50155, Class S1, no battery installed
<b>Protective Earthing</b>	Supported
<b>Power Connector</b>	M12 S-coded male
<b>Reverse Polarity Protection</b>	Supported

**ENVIRONMENTAL CONDITIONS**

<b>Operating Temperature</b>	-25 to 70°C (EN 50155 class T3)
<b>Extended Operating Temperature</b>	EN 50155 class ST0 (no extended temperature range)
<b>Storage Temperature</b>	-40 to 85°C
<b>Shock and vibration</b>	EN 50155, category 1, class B (testing according to EN 61373)
<b>IP Level</b>	IP20
<b>Railway Fire Protection</b>	EN 45545-2 HL3
<b>Pollution Degree</b>	EN 50124-1 PD2

**STANDARDS AND CERTIFICATIONS**

<b>Shock and Vibration</b>	EN 61373:2012
<b>EMC</b>	EN 61000-6-2 EN 61000-6-4 Compliant with ECE-R10 regulations
<b>EMS</b>	EN 61000-4-2 EN 61000-4-3 EN 61000-4-4 EN 61000-4-5 EN 61000-4-6
<b>CE</b>	2014/30/EU (Electromagnetic Compatibility Directive) 2014/35/EU (Low Voltage Directive) 2011/65/EU (RoHS)
<b>Railway</b>	EN 50155, EN 50121-3-2
<b>Railway Fire Protection</b>	EN 45545-1, EN 45545-2 HL3, EN 45545-5 EN 50124-1 PD2 EN 50159, category 1 EN 50165 class 1
<b>Safety Integrity Level</b>	Hardware applicable for SIL2 applications

**MECHANICAL DATA**

<b>Dimensions (W/L/H)</b>	295 × 96 × 129 mm (housing) 96 x 129 mm (front panel)
<b>Housing</b>	Sheet steel
<b>Weight</b>	2.8 kg (depending on configuration)
<b>Installation</b>	Mounted on 19" 3HU sub-rack using 4 screws 5 units per 3HU Maximum installation depth: 305 mm (required), 325 – 345 mm (recommended)
<b>Cooling</b>	External fan required

## THERE IS ALWAYS A **MISSION EMBEDDED**

Mission Embedded develops and supplies highly reliable embedded systems for professional applications in safety-critical areas such as railway and transportation, special vehicles, industry, medical technology as well as aerospace and defense. Our high-quality tailor-made solutions enable our customers to turn their innovation projects into reality within the shortest possible time.

© Mission Embedded GmbH. All rights reserved. V1.0 – 2024

This document or parts of it may not be reproduced or otherwise used without the explicit and written permission of Mission Embedded GmbH. Product specifications subject to change without notice.